

Blue Mountain Co  
PLUMBING

# Temporary Downpipe



## Installation and Specification Guide

### PRODUCT DETAILS

Temporary Downpipe is a safe, versatile and effective way to re-direct rain and storm water away from building sites or when cleaning roofs and gutters.

**ST0023** 190mm wide x 25mtr roll

### FEATURES AND BENEFITS

- Attach to the gutter outlet and run to a stormwater discharge point
- Increase safety for all trade aspects working in wet conditions
- Prevents structural damage and movement, such as slab heave, by keeping foundations dry during construction
- Time efficient and cost effective answer to council requirements for environmental protection, sediment and erosion control on building sites
- Manufactured from LLDPE
- UV stabilized
- Logo reprinted every 500mm for easy measuring

# Installation

---

## WHAT'S IN THE BOX?

- Temporary Downpipe roll (25m or 360m)

## TOOLS/MATERIALS YOU MAY REQUIRE

- Utility knife
- Tape

---

## TEMPORARY DOWNPIPE

1. Ensure your gutter drops/outlets are clean.
2. Cut your Temporary Downpipe to the desired length.
3. Place over your gutter drops and securely tape in place.

---

## PRODUCT DIMENSIONS



Material thickness 100µm

ALL DIMENSIONS IN MM UNLESS OTHERWISE STATED.

Fitment

---

Temporary Downpipe Suits up to 100m outlets (downpipes)

---

DISCLAIMER This product specification is not a complete guide to product usage. Product specifications may change without notice. For more information visit [rainharvesting.com.au](http://rainharvesting.com.au). Keep this manual handy for future reference. © Rain Harvesting Pty Ltd.

---

**Blue Mountain Co**  
PLUMBING

+61 (0)7 3248 9600

[bluemountain.com.au/plumbing](http://bluemountain.com.au/plumbing)